

E31 Rear spring cut comparison

5-Jan-09

comp	H&R	lb/inch	CI	lb/inch	3/4T cut	lb/inch	1T cut	lb/inch	Eibach	lb/inch	M tech	lb/inch	CSI	lb/inch	DinanIII	lb/inch	test range
0																	12 inches
0.25	75		95		101		93		89		96		132				
0.5	154		186		199		189		188		208		257		70		
0.75	239		277		298		291		290		329		382		171		
1	318	318	369	369	397	397	394	394	396	396	455	455	515	517	280	280	
1.25	398		469		500		497		502		583		660		420		
1.5	482		562		601		602		608		712		801		602		
1.75	557		656		702		707		715		842		940		753		
2	638	320	747	378	804	407	812	418	822	426	971	516	1092	575	923	667	
2.25	720		841		906		916		930		1101		1244		1097		
2.5	804		937		1009		1023		1038		1233		1408		1275		
2.75	889		1033		1111		1128		1147		1364		1589		1453		
3	970	332	1129	383	1213	409	1233	421	1256	434	1498	527	1752	660	1634	711	
3.25	1057		1225		1316		1340		1366		1632		1928		1812		
3.5	1141		1321		1420		1448		1476		1765		2096		1994		
3.75	1225		1420		1525		1556		1585		1901		2276		2177		
4	1310	340	1520	398	1628	415	1662	429	1695	439	2037	539	2450	698	2360	726	8 inches

